

55" Touch Screen Dual Digital Signage Standee

Right message at the right time

JXD DDS550PCT



Specifications

PANEL	Panel Type	55" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG
PC SPECIFICATION	Max Resolution	1920 x 1080	TOUCH	USB Playback Video	M2TS, M4V, MK3D, MKV, MP4, MPEG MPG, MTS, TS, TTS, VOB, WMV
	Aspect Ratio	16:9 (Portrait / Landscape)			
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz 100W
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W
	Response Time	8ms		TEMPERATURE	Operating Temperature
	Display Area	1238 x 714mm		Storage Temperature	-20°C to 60°C
	Panel Size	1905 x 796 x 200mm	DIMENSION & WEIGHT	Standee Size	1905 x 796 x 200mm
	CPU	Intel Celeron Quad Core Processor, 2.0 Ghz		Base	796 x 48 x 500mm
	Chipset	Intel HM76		Standee Weight	200kg
	BIOS	Intel HD Graphics 4000		Base Weight	12.5kg
OS	Windows 10 IOT	STRUCTURE	Material	MS Steel Plate Frame	
Memory	4GB RAM, 120GB SSD		Thickness	1.2 - 1.5mm Slim Smart Design	
Audio	Realtek ALC662	FEATURE		Moistureproof, Anti-rust treatment, Anti-dust, Static Free	
Ethernet LAN	2 x RTL8111e LAN		ACCESSORIES	Castor, User Manual, Keys, Tools & Screws	
CONNECTOR	Rear Panel I/O	HDMI x 1			
		VGA x 1			
CONNECTIVITY	LAN	RJ45 Port, 10/100m Ethernet			
		WiFi	Built-in WiFi 802.11B B/G/N		
		3G (Optional)	WCDMA		