

# 65" Touch Screen Dual Digital Signage Standee

Right message at the right time

**JXD DDS650PCT**



## Specifications

PANEL	Panel Type	65" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA	
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG	
PC SPECIFICATION	Max Resolution	1920 x 1080	USB Playback Video	M2TS, M4V, MK3D, MKV, MP4, MPEG	MPG, MTS, TS, TTS, VOB, WMV	
	Aspect Ratio	16:9 (Portrait / Landscape)	TOUCH	Multi 10 points IR touch		
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz	100W
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W	
	Response Time	8ms	TEMPERATURE	Operating Temperature	0°C to 40°C	
	Display Area	1456 x 838mm		Storage Temperature	-20°C to 60°C	
	Panel Size	2200 x 900 x 200mm	DIMENSION & WEIGHT	Standee Size	2200 x 900 x 200mm	
				Base	900 x 48 x 500mm	
				Standee Weight	240kg	
				Base Weight	15kg	
	CONNECTOR	Rear Panel I/O	HDMI x 1 VGA x 1 RJ-45 x 1 USB 2.0 x 1 USB 3.0 x 1 Audio I/O (Mic & Line Out)	STRUCTURE	Material	MS Steel Plate Frame
CONNECTIVITY	LAN	RJ45 Port, 10/100m Ethernet	Thickness	1.2 - 1.5mm Slim Smart Design		
	WiFi	Built-in WiFi 802.11B B/G/N	FEATURE	Moistureproof, Anti-rust treatment, Anti-dust, Static Free		
	3G (Optional)	WCDMA	ACCESSORIES	Castor, User Manual, Keys, Tools & Screws		