

49" Touch Screen Digital Signage Standee

JXD DS495PCT

Right message at the right time



Specifications

PANEL	Panel Type	49" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA	
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG	
PC SPECIFICATION	Max Resolution	1920 x 1080	USB Playback Video	M2TS, M4V, MK3D, MKV, MP4, MPEG	MPG, MTS, TS, TTS, VOB, WMV	
	Aspect Ratio	16:9 (Portrait / Landscape)	TOUCH	Multi 10 points IR touch		
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz 140W	
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W	
	Response Time	8ms	TEMPERATURE	Operating Temperature	0°C to 40°C	
	Display Area	1102 x 638mm		Storage Temperature	-20°C to 60°C	
	Panel Size	1873 x 718 x 65mm	DIMENSION & WEIGHT	Standee Size	1873 x 718 x 65mm	
	CPU	Intel Celeron Quad Core Processor, 2.0 Ghz		Base	718 x 48 x 460mm	
	Chipset	Intel HM76		Standee Weight	98kg	
	BIOS	Intel HD Graphics 4000		Base Weight	12.5kg	
OS	Windows 10 IOT	CONNECTIVITY	LAN	RJ45 Port, 10/100m Ethernet		
Memory	4GB RAM, 120GB SSD		WiFi	Built-in WiFi 802.11B B/G/N		
Audio	Realtek ALC662		3G (Optional)	WCDMA		
Ethernet LAN	2 x RTL8111e LAN	STRUCTURE	Material	MS Steel Plate Frame		
CONNECTOR	Rear Panel I/O		Thickness	1.2 - 1.5mm Slim Smart Design		
			Glass	4mm thickness tempered glass		
	HDMI x 1	FEATURE	Moistureproof, Anti-rust treatment, Anti-dust, Static Free			
	VGA x 1	ACCESSORIES	Castor, User Manual, Keys, Tools & Screws			
	RJ-45 x 1					
	USB 2.0 x 1					
	USB 3.0 x 1					
	Audio I/O (Mic & Line Out)					