

55" Digital Signage Standee

Right message at the right time


JXD DS555PC



Specifications

PANEL	Panel Type	55" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG
PC SPECIFICATION	Max Resolution	1920 x 1080	USB Playback Video	M2TS, M4V, MK3D, MKV, MP4, MPEG	MPG, MTS, TS, TTS, VOB, WMV
	Aspect Ratio	16:9 (Portrait / Landscape)	TOUCH	Nil	
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz 140W
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W
	Response Time	8ms	TEMPERATURE	Operating Temperature	0°C to 40°C
	Display Area	1238 x 714mm		Storage Temperature	-20°C to 60°C
	Panel Size	1905 x 796 x 65mm	DIMENSION & WEIGHT	Standee Size	1905 x 796 x 65mm
	CPU	Intel Celeron Quad Core Processor, 2.0 Ghz		Base	796 x 48 x 460mm
	Chipset	Intel HM76		Standee Weight	115kg
	BIOS	Intel HD Graphics 4000		Base Weight	12.5kg
OS	Windows 10 IOT	STRUCTURE	Material	MS Steel Plate Frame	
Memory	4GB RAM, 120GB SSD		Thickness	1.2 - 1.5mm Slim Smart Design	
Audio	Realtek ALC662		Glass	4mm thickness tempered glass	
Ethernet LAN	2 x RTL8111e LAN	FEATURE	Moistureproof, Anti-rust treatment, Anti-dust, Static Free		
CONNECTOR	Rear Panel I/O	LAN	RJ45 Port, 10/100m Ethernet		
		WiFi	Built-in WiFi 802.11B B/G/N		
		3G (Optional)	WCDMA		
		ACCESSORIES	Castor, User Manual, Keys, Tools & Screws		

Distributed by



JD Molecule Sdn Bhd | 16B, Jalan Astaka U8/L, Bukit Jelutong, 40150 Shah Alam Selangor | www.jdmolecule.com

Recommended Backend CMS

NAVORI
DIGITAL SIGNAGE ENGINE

Specifications are subject to change without prior notice
Trademarks are the property of their respective owners
Copyright © 2018 All Rights Reserved

Version 1.2