

65" Touch Screen Digital Signage Standee

JXD DS655PCT

Right message at the right time



Specifications

PANEL	Panel Type	65" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG
PC SPECIFICATION	Max Resolution	1920 x 1080	USB Playback Video	MPG, MTS, TS, TTS, VOB, WMV	
	Aspect Ratio	16:9 (Portrait / Landscape)	TOUCH	Multi 10 points IR touch	
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz 100W
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W
	Response Time	8ms	TEMPERATURE	Operating Temperature	0°C to 40°C
	Display Area	1456 x 838mm		Storage Temperature	-20°C to 60°C
	Panel Size	2200 x 900 x 90mm	DIMENSION & WEIGHT	Standee Size	2200 x 900 x 90mm
	CPU	Intel Celeron Quad Core Processor, 2.0 Ghz		Base	900 x 48 x 500mm
	Chipset	Intel HM76		Standee Weight	125kg
	BIOS	Intel HD Graphics 4000		Base Weight	15kg
OS	Windows 10 IOT	STRUCTURE	Material	MS Steel Plate Frame	
Memory	4GB RAM, 120GB SSD		Thickness	1.2 - 1.5mm Slim Smart Design	
Audio	Realtek ALC662	FEATURE		Moistureproof, Anti-rust treatment, Anti-dust, Static Free	
Ethernet LAN	2 x RTL8111e LAN	ACCESSORIES		Castor, User Manual, Keys, Tools & Screws	
CONNECTOR	Rear Panel I/O	HDMI x 1			
		VGA x 1			
		RJ-45 x 1			
		USB 2.0 x 1			
		USB 3.0 x 1			
		Audio I/O (Mic & Line Out)			
CONNECTIVITY	LAN	RJ45 Port, 10/100m Ethernet			
	Wifi	Built-in Wifi 802.11B B/G/N			
	3G (Optional)	WCDMA			

Recommended Backend CMS

NAVORI LABS
DIGITAL SIGNAGE ENGINE

Specifications are subject to change without prior notice
Trademarks are the property of their respective owners
Copyright © 2018 All Rights Reserved

Version 1.2